

Gravity Handler

Hot tests, RF tests, vision inspections, or laser marking can be installed.

RT and Hot Test

Features

- High throughput, no jamming, small footprint
- Large capacity loader/unloader for high-volume production
- Large test head can be installed
- Fast changeover by parts unitization
- Socket test available



Specifications

Model	TH281
Device	SOP, SSOP, TSSOP, DIP, etc
Throughput	0.9sec/pc(Test time 0.3sec)
Input	Magazine or single-tube
Test	• Hot or RT : 2 stations
Laser mark	—
Vision inspection	—
Output	Magazine: 4 lanes

RF Test

Features

- Applicable to high-volume production using large test boxes
- Max 4 test stations can be connected to different test boxes
- Easy changeover
- Lead inspection available (option)



Specifications

Model	TH285
Device	SOP, SSOP, TSSOP, DIP, etc
Throughput	0.9sec/pc(Test time 0.3sec)
Input	Magazine or single-tube
Test	Max 4 stations (Hot test available)
Laser mark	—
Vision inspection	Lead inspection (option)
Output	Magazine: 4 lanes

Hot Test

Features

- High speed / small footprint
- Applicable to high-volume production using large test boxes
- Max 3 test stations can be connected to different test boxes
- Lead inspection available (option)



Specifications

Model	TH233C
Device	TO220, TO126, TO3P, SIP, etc
Throughput	2.0sec/pc (Test time 1.0sec)
Input	Magazine or single-tube
Test	Hot : 3 station
Laser mark	—
Vision inspection	—
Output	Magazine: 6 lanes

Simple type

Features

- Simple type with RT test and laser marking
- Manual tube supply/discharge
- Customer-designated laser marker applicable
- Laser mark inspection (option)



Specifications

Model	TM226
Device	SOP, SSOP, TSSOP, DIP, etc
Throughput	0.9sec/pc
Input	Tube (10 tubes manual supply)
Test	Max 1 station
Laser mark	Package top surface
Vision inspection	Laser mark inspection (option)
Output	Tube: 14 lanes